Data-driven discovery of drag-inducing elements on a rough surface through convolutional neural networks

Heesoo Shin¹, Seyed Morteza Habibi Khorasani², Zhaoyu Shi², Jiasheng Yang³, Sangseung Lee¹[†], and Shervin Bagheri²

¹Department of Mechanical Engineering, Inha University, Incheon 22212, Republic of Korea ²FLOW, Department of Engineering Mechanics, KTH, Stockholm SE-100 44, Sweden ³Institute of Fluid Mechanics, Karlsruhe Institute of Technology, Karlsruhe 76131, Germany

(Received xx; revised xx; accepted xx)

Understanding the influence of surface roughness on drag forces remains a significant challenge in fluid dynamics. This paper presents a convolutional neural network (CNN) that predicts drag solely by the topography of rough surfaces and is capable of discovering spatial patterns linked to drag-inducing structures. A CNN model was developed to analyze spatial information from the topography of a rough surface and predict the roughness function, ΔU^+ , obtained from direct numerical simulation. This model enables the prediction of drag from rough surface data alone, which was not possible with previous methods owing to the large number of surface-derived parameters. Additionally, the retention of spatial information by the model enables the creation of a feature map that accentuates critical areas for drag prediction on rough surfaces. By interpreting the feature maps, we show that the developed CNN model is able to discover spatial patterns associated with drag distributions across rough surfaces, even without a direct training on drag distribution data. The analysis of the feature map indicates that, even without flow field information, the CNN model extracts the importance of the flow-directional slope and height of roughness elements as key factors in inducing pressure drag. This study demonstrates that CNN-based drag prediction is grounded in physical principles of fluid dynamics, underscoring the utility of CNNs in both predicting and understanding drag on rough surfaces.

Key words: Authors should not enter keywords on the manuscript, as these must be chosen by the author during the online submission process and will then be added during the typesetting process (see http://journals.cambridge.org/data/relatedlink/jfm-keywords.png for the full list)

1. Introduction

The interaction between surface roughness and fluid flow is critical, particularly in scenarios involving turbulent flows. In these flows, the roughness elements of the surface can influence the smallest eddies near the wall, often resulting in increased drag. As heightened drag impedes the optimal functioning of various systems, including turbines, vehicles, and pipelines, the precise prediction of turbulent drag on rough surfaces is crucial. While the increased drag from roughness can be determined from direct numerical simulations (DNSs) or experiments (e.g. towing tanks), these methods are not sustainable for *drag prediction* (Chung *et al.* 2021). Indeed, capturing the full nonlinear interaction between irregular roughness structures and turbulent flows may not be necessary for an accurate and reliable drag prediction.

The majority of prior studies, including those by Chan *et al.* (2015), Thakkar & Busse (2017), Forooghi *et al.* (2017), and Flack & Schultz (2020*a*), developed empirical relations that establish a correlation between drag and statistical surface parameters, such as skewness, effective slope and mean roughness height. Although these models present a good fit of the empirical data which they were developed for, they often poorly predict the drag of surfaces of different roughness types. The topographic data of rough surfaces, typically represented by two-dimensional height-map, could not be directly used in the empirical models owing to their large size. Instead, the surfaces had to be parameterized by statistical means, which does not capture all the spatial details of the surface topography. In addition, statistical parameterization complicates the identification of structural patterns on rough surfaces relevant to drag and reduces the physical interpretability of the predictive model.

A second aspect is related to the modelling approach itself, since the accuracy of predictions depends significantly on capacity of the models. Recent developments have used artificial neural networks (ANNs), which are adept at managing complex, nonlinear problems. Studies by Jouybari *et al.* (2021) and Lee *et al.* (2022) have demonstrated the potential of fully connected networks (FCNs) in predicting drag on rough surfaces. Nonetheless, these models still depend on the statistical parameters of surface topography, which limits their ability to use the actual rough surface as an input. Consequently, this study aims to overcome these obstacles by directly employing surface topography for drag prediction using convolutional neural networks (CNNs), focusing not on predictive accuracy but on the methodology itself. Given their ability to recognize spatial patterns, CNNs have been applied in various fluid engineering research areas (Lee 2019; Murata & Fukami 2020; Morimoto *et al.* 2021; Santos *et al.* 2020; Deo 2022).

In this study, we developed a CNN model, trained on a DNS dataset of turbulent flows over both isotropic and anisotropic rough surfaces, to predict the roughness function (ΔU^+) . This function represents the difference in the mean velocity profiles between smooth- and rough-wall turbulence within the log layer (Hama 1954; Clauser 1954). We observed that the prediction of the roughness function is based on the physical mechanism by which drag is induced on rough surfaces. Although our CNN model was trained to predict the scalar quantity ΔU^+ without information about turbulent flow, it can produce feature maps that closely resemble the drag force distribution obtained through DNS. These three-dimensional matrix outputs, resulting from nonlinear operations on rough surface inputs, illustrate the correlation between surface topography and drag. By comparing these outputs with drag-force distribution maps obtained from DNS and examining different aspects of rough surface topography, we have ascertained that the CNN model predicts ΔU^+ by focusing on specific topographical features of surfaces that significantly influence the pressure drag.

The remainder of this paper is structured as follows: Section 2 describes the dataset of rough surfaces acquired through DNS, and Section 3 outlines the architecture of our CNN model. Section 4 presents the training outcomes and analyzes the ability of the CNN to identify spatial patterns associated with drag distributions, along with its limitations. Section 5 provides concluding observations and directions for future studies.

2. Rough surface dataset

This section describes the methodologies employed to create rough surface topographies and their corresponding DNS datasets, which are essential for training CNNs. It consists of two subsections: (1) the creation of rough surfaces, and (2) the computational specifics of DNS.

2.1. Generation of rough surface topographies

The rough surfaces created in this study are classified based on the topographic metrics of skewness (skw) and effective slope for both streamwise (ES_x) and spanwise (ES_z) orientations. The definitions of these topographic indicators are as follows:

$$skw = \frac{1}{A_t} \int_{x,z} (k - k_{\rm avg})^3 dA / k_{\rm rms}^3,$$
 (2.1)

$$ES_x = \frac{1}{A_t} \int_{x,z} \left| \frac{\partial k}{\partial x} \right| dA, \qquad (2.2)$$

$$ES_z = \frac{1}{A_t} \int_{x,z} \left| \frac{\partial k}{\partial z} \right| dA.$$
(2.3)

Here, x, y, and z represent the streamwise, wall-normal, and spanwise directions, respectively. Moreover, k is the distribution of roughness height and A_t denotes the total roughness plan area. Finally, k_{avg} and k_{rms} are defined as $A_t^{-1} \int_{x,z} k \, dA$ and

 $\sqrt{A_t^{-1} \int_{x,z} (k - k_{\text{avg}})^2 dA}$, respectively.

First, isotropic rough surfaces were generated featuring approximately equal values of ES_x and ES_z . Three categories of isotropic surfaces were generated: (i) Gaussian (zero-skw), (ii) positive-skw, and (iii) negative-skw rough surfaces. These surfaces are distinguished based on their skw value, which reflects the asymmetry in the distribution of k. Gaussian rough surfaces (S_{Gauss}) have a Gaussian distribution of k, leading to an evenly balanced distribution of peaks and valleys and a skw value of zero. Positive-skw rough surfaces (S_{pos}) consist of planes and peaks, resulting in positive skw values. In contrast, negative-skw rough surfaces (S_{neg}) are characterized by planes and pits and yield negative skw values. In figure 1, ES_x is the same as ES_z for all surfaces, with the S_{Gauss} sample indicating that skw equals zero, whereas the S_{pos} and S_{neg} samples differ. These isotropic surfaces were created using the Fourier-filtering algorithm and the code developed by Jacobs & Junge (2017).

Second, we generated anisotropic rough surfaces, which – unlike isotropic surfaces – exhibit directionality, leading to differences between ES_x and ES_z . To create these surfaces, we employed the multiscale anisotropic rough surface algorithm developed by Jelly (2019). We produced (i) ES_x -dominant anisotropic rough surfaces (S_{ES_x}) and (ii) ES_z -dominant anisotropic rough surfaces (S_{ES_z}). In figure 2, the S_{ES_x} sample shows larger ES_x values compared with ES_z , leading to wave-like patterns in the streamwise direction. Conversely, the S_{ES_z} sample has larger ES_z values than ES_x , resulting in wave-like patterns in the spanwise direction. The skewness (skw) of both surfaces is zero.

Each surface type consists of 135 surfaces, which were doubled through the augmentation method described in Appendix C, yielding 270 surfaces. In addition, we added 162 hydrodynamically smooth surfaces, as detailed in Appendix C. The surfaces were subsequently divided into datasets: 60% for training, 20% for validation, and 20% for testing, as detailed in Appendix C.



Figure 1: Visualization of (a) S_{Gauss} , (b) S_{pos} , and (c) S_{neg} in 3D (upper row) and 2D (lower row).



Figure 2: Visualization of (a) S_{ES_x} and (b) S_{ES_z} in 3D (upper row) and 2D (lower row).

2.2. Direct numerical simulations

We developed a dataset of rough-wall turbulence in both the transitionally and fully rough regimes by solving the incompressible Navier-Stokes equations, as follows:

$$\nabla \cdot \mathbf{u} = 0 \tag{2.4}$$

$$\frac{\partial \mathbf{u}}{\partial t} + \nabla \cdot (\mathbf{u}\mathbf{u}) = -\frac{1}{\rho}\nabla p + \nu \nabla^2 \mathbf{u} - \frac{1}{\rho}P_x \mathbf{e_x} + \mathbf{f}_{\text{IBM}}$$
(2.5)

where $\mathbf{u} = (u, v, w)^{\mathsf{T}}$ is the velocity vector, and P_x is the mean pressure gradient and $\mathbf{e_x}$ the streamwise unit vector. P_x is added as a constant source term to the momentum equation to drive the flow in the channel. p denotes the pressure fluctuations, $\mathbf{e_x}$ denotes the streamwise basis vector, ρ denotes the density (set to 1 in this study), ν denotes the kinematic viscosity, and \mathbf{f}_{IBM} denotes the body-force term introduced

by the immersed boundary method (IBM) to enforce the no-slip and no-penetration conditions on the rough surfaces (Kajishima et al. 2001). For solving these equations, we used the open-source GPU-accelerated solver CaNS (Costa et al. 2021). This solver is spatially second-order accurate and employs a fast Poisson solver, and temporally integrates the Navier-Stokes equations using a three-step Runge-Kutta scheme as part of a fractional-step algorithm (Kim 1985). We adopted a minimal channel approach to minimize computational expenses while ensuring accurate results for ΔU^+ (Chung et al. 2015). The simulations in the minimal-channel rough-wall DNS were conducted at a friction Reynolds number $Re_{\tau} = u_{\tau}\delta/\nu = 500$, where δ represents the channel halfheight, and u_{τ} represents the friction velocity. Periodic boundary conditions were used along the x- and z-directions, with a Dirichlet boundary condition along the y-direction. The domain dimensions L_x , L_z , and L_y were set to 2.4 δ , 2.0 δ , and 0.8 δ , respectively. The numbers of grid points in the x- (N_x) and z- (N_z) directions were fixed at 302 and 102, respectively, with the grid spacings in the x- and z-directions in the viscous scale (Δx^+ and Δz^+) being 4.192 and 4.137, respectively. The superscript + indicates normalization by the viscous scale $\delta_{\nu} = \nu/u_{\tau}$. In the y-direction, the grid was stretched using the hyperbolic tangent function with a minimum y^+ value ≈ 0.5 . These grid sizes are confirmed by the grid convergence tests described in Appendix A to ensure sufficient accuracy.

The DNS results were used to obtain ΔU^+ , following the methodology described by Yang *et al.* (2022).

The logarithmic mean velocity profile, U^+ , is expressed as:

$$U_R^+ = \frac{1}{\kappa} \ln(y^+) + A + \Delta U^+ = U_S^+ + \Delta U^+, \qquad (2.6)$$

where $\kappa \approx 0.4$ and A is the von Kármán constant and log-law intercept for a smooth surface (approximately 5.0). The subscripts S and R denote smooth and rough surface quantities, respectively. The function ΔU^+ depends on both the roughness topography and the roughness size, k^+ . The latter is defined as:

$$k^+ = \frac{k}{\delta_\nu} = \frac{ku_\tau}{\nu}.$$
(2.7)

We determine $\Delta U^+ = U_R^+ - U_S^+$ at a designated reference point of $y^+ = 200$, as depicted in figure 3, where ΔU^+ achieves a fixed value. A positive ΔU^+ indicates a momentum loss attributable to surface roughness, whereas a negative value indicates a momentum gain. Thus, ΔU^+ serves as an indicator for drag resulting from surface roughness. Accordingly, our CNN model was trained to predict ΔU^+ .

Using DNS, we investigated the relationship between the topographical characteristics of rough surfaces and ΔU^+ across different surface types. Figure 4(a) shows the distribution of each surface as a function of ES_x and ES_z . It is clear that the isotropic surfaces ($S_{Gauss}, S_{pos}, S_{neg}$) discussed earlier are distributed on the line $ES_x = ES_z$. Figure 4(b) shows the distribution of ΔU^+ relative to the ES_x values of the surfaces, revealing a positive correlation between an increase in ES_x and a corresponding rise in ΔU^+ . A notable exception is S_{neg} . The mechanism of drag generation on the S_{neg} surface is distinct from that on other surfaces; consequently, we analyze the case of S_{neg} separately in a section 4.4. Figure 4(c) shows that ES_z is positively correlated with ΔU^+ for S_{pos}, S_{Gauss} , and S_{ES_x} , mirroring the trend observed between ES_x and ΔU^+ . However, variations in ES_z do not significantly affect ΔU^+ . This is attributed to the fact that an increase in ES_z typically results in an increase in ES_x for S_{Gauss}, S_{pos} , and S_{ES_x} , but not for S_{ES_z} . In the case of S_{neg} , an increase in ES_z exerts a negligible



Figure 3: U_S^+ , U_R^+ , and ΔU^+ of the S_{Gauss} sample.

influence. Thus, these findings underscore that an enhancement in ES_x generally leads to an increase in ΔU^+ . This relationship is due to ES_x being directly proportional to twice the value of frontal solidity (λ_f) , a measure reflecting the area exposed to pressure drag (Chung *et al.* 2021). Finally, figure 4(d) illustrates the distribution of ΔU^+ relative to the *skw* values of the surfaces. Notably, S_{neg} shows significantly lower ΔU^+ , ranging between 1 and 2, in contrast to the typical range of 3–8 observed for most surfaces.

Our aim is not only to predict ΔU^+ but also to demonstrate that our model trained to predict ΔU^+ learns the dominant drag-inducing mechanisms. We extracted drag maps from DNS to provide a detailed visual representation of drag force distribution on the rough surface. Figure 5 shows an example of a DNS-derived drag map, f_x , where f_x is the streamwise component of the wall-integrated mean IBM force,

$$(f_x, f_y, f_z)^{\mathsf{T}} = -\frac{1}{T} \int_0^H \int_0^T \mathbf{f}_{\text{IBM}}(x, y, z, t) dt dy.$$
 (2.8)

The negative sign indicates that the forces act in the opposite direction of the flow. An overall increase in the magnitude of f_x signifies a loss of the streamwise momentum, correlating with an increase in ΔU^+ . From in figure 5, we note that the regions where the roughness significantly contribute to drag are spanwise elongated.

These DNS drag maps provide a means for both quantitative and qualitative evaluations in comparison with the feature maps produced by the CNN model. This comparison enhances our understanding of the effectiveness of the model and the physical phenomena it encapsulates. To assess the ability of the CNN to accurately reflect the physics across different rough surface types, we obtained DNS drag maps for three samples from each rough surface category, which were not used in training the model ($S_{Gauss,i}, S_{pos,i}, S_{neg,i}, S_{ES_x,i}$, and $S_{ES_x,i}$, where i = 1, 2, 3).

3. CNN architecture

In contrast to FCNs used in previous studies (Lee *et al.* 2022; Jouybari *et al.* 2021), CNNs can process high-dimensional data for training without omitting the spatial infor-



Figure 4: (a) Correlation between ES_x and ES_z for different rough surfaces. (b) Correlation between ES_x and ΔU^+ for each surface. (c) Correlation between ES_z and ΔU^+ for each surface; the linear regression for each cluster is denoted by its lines in (b) and (c). (d) Correlation between skw and ΔU^+ for different rough surfaces



Figure 5: Visualization of f_x corresponding to the rough surface in figure 1 (a).

mation contained within, owing to convolutional operations. In this study, we developed a deep neural network based on the CNN framework to preserve the spatial information of rough surfaces and directly utilize it as input.

Figure 6 shows the detailed CNN model architecture used in this study. Regarding the structure of the model, this section will focus on two architectural elements introduced specifically to deal with rough surfaces: periodic boundary conditions and a parallel structure. For additional information on other structural features of the model, refer to Appendix B. Moreover, the CNN model was trained using training and validation datasets, and its hyperparameters were finetuned through Bayesian optimization, as detailed in Appendix D.

Since zero values exist at the edges of the surface data due to the traditional zeropadding method, which differs from the DNS condition, we used periodic boundary padding to preserve dimensionality during convolution operations and to mimic the periodic boundary conditions observed in the DNS, specifically along the x- and zdirections. This technique expands the input feature map along the x- and z-axes, thus maintaining the cyclic nature of the boundaries in alignment with the DNS. Figure 7 shows a comparison between this padding approach and the traditional zero-padding method using an example.

Given that rough surfaces consist of roughness elements of various scales, these elements need to be considered in predicting drag. In this context, the parallel structure of our CNN is designed to detect roughness elements at various scales. Applying the inception module introduced by Szegedy *et al.* (2015), our CNN model utilizes a range of kernel sizes from 3×3 to 11×11 , corresponding to the grid sizes. This diversity facilitates the detection of surface features at multiple scales. As depicted in figure 6, toward the end of the CNN, feature maps from different kernels within the parallel structure were merged. This was followed by a convolution with a 1×1 kernel employing a single filter, a process that combines the features while maintaining the original input dimensions. Subsequently, a comprehensive CNN feature map was produced. This map was subject to global average pooling (GAP), generating a scalar value representative of ΔU^+ .

4. Evaluation of prediction performance and physics learnability

Next, we evaluate the trained CNN model from two perspectives: its accuracy in predicting ΔU^+ , and its ability to capture the mechanisms of drag induced on rough surfaces. The latter entails generating feature maps that that can be gauged against the drag force distributions of the DNS drag maps. As the topographical, CNN feature, and DNS drag maps depict distributions of k^+ , ΔU^+ , and f_x , respectively, we standardized each map using the following equation:

$$\tilde{\boldsymbol{m}} = \frac{\boldsymbol{m} - \mu}{\sigma},\tag{4.1}$$

where $\tilde{\boldsymbol{m}}$ represents the standardized form of a given map (\boldsymbol{m}), which is a two-dimensional matrix, μ is the mean of \boldsymbol{m} , and σ is the standard deviation of \boldsymbol{m} .

4.1. ΔU^+ prediction performance of the CNN model

The evaluation of the predictive accuracy of the model for ΔU^+ is quantified using the mean absolute error (MAE) and the coefficient of determination (R^2). The MAE is defined as follows:

MAE =
$$\frac{1}{N} \sum_{i=1}^{N} |y_i - \tilde{y}_i|,$$
 (4.2)



Figure 6: Illustration of CNN architecture utilized in this study.



Figure 7: (a) and (b) Original feature map in blue: (a) zero padding areas (in red), (b) domain expanded via periodic padding (in yellow).

	MAE	MAPE(%)	Max.AE
S_{Gauss}	0.111	1.797	0.407
S_{pos}	0.128	2.698	0.372
S_{neg}	0.062	4.075	0.229
S_{ES_x}	0.149	2.431	0.579
$S_{ES_{\pi}}$	0.145	1.961	0.433

Table 1: MAE, MAPE, and maximum absolute error (Max.AE) of the ΔU^+ prediction by the CNN model for each surface type in the test dataset.

where N represents the number of samples in the test dataset, y_i is the actual ΔU^+ , and \tilde{y}_i is the ΔU^+ predicted by the CNN model. The R^2 metric is defined as

$$R^{2} = 1 - \frac{\sum_{i=1}^{N} (y_{i} - \tilde{y}_{i})^{2}}{\sum_{i=1}^{N} (y_{i} - \overline{y})^{2}},$$
(4.3)

where \overline{y} is the average of the actual ΔU^+ . Lower MAE values indicate an improved predictive accuracy. An R^2 value close to 1 signifies high precision, whereas a value close to 0 indicates lower reliability. The average prediction accuracy across all the surface types was 0.108 in terms of the MAE and 0.996 in terms of R^2 . Additionally, the prediction accuracy for each type of surface is detailed in table 1. In this table, we used the mean absolute percentage error (MAPE) to indicate the accuracy for each surface type. The MAPE is defined as

MAPE(%) =
$$\frac{1}{N} \sum_{i=1}^{N} \frac{|y_i - \tilde{y}_i|}{y_i} \times 100,$$
 (4.4)

According to the table 1, all the surface types demonstrated a comparable prediction accuracy. However, S_{neg} showed larger errors compared with the other types of surfaces. The reasons for the larger errors specifically in predicting drag on S_{neg} are discussed in Section 4.4. The ability of the CNN model to capture drag generation factors for various surface types and generate feature maps resembling their drag distribution is validated and analyzed in Sections 4.2 to 4.3.

4.2. Assessment of physics learnability through feature map analysis

This section evaluates the ability of the CNN model to capture the main physics of drag inducement across four different surface types $(S_{Gauss}, S_{pos}, S_{ES_x}, \text{and } S_{ES_z})$. These surface type demonstrate a comparable predictive performance (table 1). As DNS drag maps originate from solutions to the Navier–Stokes equations, a CNN feature map that closely resembles the DNS drag map suggests that the CNN model effectively captures the mechanisms of drag generation on rough surfaces. Therefore, we evaluated the similarity between the CNN feature maps and the DNS drag maps.

To evaluate the similarity between the CNN feature maps and the DNS drag maps, or between the CNN feature maps and the topographical maps, we calculated the root mean squared error (RMSE) and structural similarity index measure (SSIM). The RMSE is defined as

RMSE =
$$\sqrt{\frac{1}{N_x N_z} \sum_{i=1}^{N_x} \sum_{j=1}^{N_z} (\boldsymbol{a}_{i,j} - \boldsymbol{b}_{i,j})^2},$$
 (4.5)

where $\boldsymbol{a}_{i,j}$ and $\boldsymbol{b}_{i,j}$ represent arbitrary maps. These could be any two among a CNN map, a DNS drag map, or a topographical map.

The SSIM was originally a method for comparing the similarity between two images, devised by Wang *et al.* (2004). The method evaluates the similarity based on three components of the image: luminance (l), contrast (c), and structure (s). In this study, these components are interpreted as follows: (i) l represents regions of higher or lower map values, (ii) c denotes areas with significant variations in map values, and (iii) s evaluates the spatial arrangement of map values, corresponding to the organization of patterns across the map. The SSIM is defined as:

$$l(\mathbf{a}_{i,j}, \mathbf{b}_{i,j}) = \frac{2\mu_{a_{i,j}}\mu_{b_{i,j}} + c_1}{\mu_{a_{i,j}}^2 + \mu_{b_{i,j}}^2 + c_1},$$
(4.6)

$$c(\mathbf{a}_{i,j}, \mathbf{b}_{i,j}) = \frac{2\sigma_{a_{i,j}}\sigma_{b_{i,j}} + c_2}{\sigma_{a_{i,j}}^2 + \sigma_{b_{i,j}}^2 + c_2},$$
(4.7)

$$s(\mathbf{a}_{i,j}, \mathbf{b}_{i,j}) = \frac{\sigma_{a_{i,j}b_{i,j}} + c_3}{\sigma_{a_{i,j}}\sigma_{b_{i,j}} + c_3},$$
(4.8)

where

$$\mu_{a_{i,j}} = \frac{1}{N_x N_z} \sum_{i=1}^{N_x} \sum_{j=1}^{N_z} \boldsymbol{a}_{i,j},$$
(4.9)

$$\mu_{b_{i,j}} = \frac{1}{N_x N_z} \sum_{i=1}^{N_x} \sum_{j=1}^{N_z} \mathbf{b}_{i,j}, \qquad (4.10)$$

$$\sigma_{a_{i,j}}^2 = \frac{1}{N_x N_z} \sum_{i=1}^{N_x} \sum_{j=1}^{N_z} (\mathbf{a}_{i,j} - \mu_{a_{i,j}})^2, \tag{4.11}$$

$$\sigma_{b_{i,j}}^2 = \frac{1}{N_x N_z} \sum_{i=1}^{N_x} \sum_{j=1}^{N_z} (\mathbf{b}_{i,j} - \mu_{b_{i,j}})^2, \qquad (4.12)$$

$$\sigma_{a_{i,j}b_{i,j}} = \frac{1}{N_x N_z (N_x N_z - 1)} \sum_{i=1}^{N_x} \sum_{j=1}^{N_z} (\boldsymbol{a}_{i,j} - \mu_{a_{i,j}}) (\boldsymbol{b}_{i,j} - \mu_{b_{i,j}}).$$
(4.13)



Figure 8: Comparison of maps for each surface type: (a) $S_{Gauss,1}$, (b) $S_{pos,1}$, (c) $S_{ES_{x,1}}$, and (d) $S_{ES_{z,1}}$.

Here, $c_1 = (k_1L)^2$, $c_2 = (k_2L)^2$, and $c_3 = c_2/2$ with $k_1 = 0.01$ and $k_2 = 0.03$, and L is defined as the difference between the maximum and minimum values among $\boldsymbol{a}_{i,j}$ and $\boldsymbol{b}_{i,j}$. The overall SSIM index was computed as the product of these three components:

$$\mathrm{SSIM}(\boldsymbol{a}_{i,j}, \boldsymbol{b}_{i,j}) = l(\boldsymbol{a}_{i,j}, \boldsymbol{b}_{i,j})^{\alpha} \cdot c(\boldsymbol{a}_{i,j}, \boldsymbol{b}_{i,j})^{\beta} \cdot s(\boldsymbol{a}_{i,j}, \boldsymbol{b}_{i,j})^{\gamma},$$
(4.14)

where the weights α , β , and γ are all 1. A SSIM value close to 1 indicates a high degree of similarity between the maps. This measure is crucial in evaluating how effectively the CNN model has captured and replicated the drag-inducing physics of the rough surfaces in the DNS.

Figure 8 displays sample topographical, DNS drag, and CNN feature maps from S_{Gauss} , S_{pos} , S_{ES_x} , and S_{ES_x} . The RMSE and SSIM values between these maps are listed in table 2. According to the table, the SSIM between the CNN feature maps and the DNS drag maps is higher than that between the CNN feature maps and the topographical maps, consistent with the lower RMSE. This indicates that the CNN feature maps resemble the DNS drag maps more closely than they do the topographical maps. Building on this assessment, we investigated the high-intensity patterns in the CNN feature maps and DNS drag maps. Figure 8 reveals elongated, spanwise high-intensity patterns in

12

 S_{pos} S_{ES_x} $S_{ES_{z}}$ S_{Gauss} MAPE (%) 1.2201.9072.003 3.090 SSIM (CNN-DNS) 0.4900.594 0.474 0.410RMSE (CNN-DNS) 0.8130.766 0.789 0.874SSIM (CNN-Topo) 0.1480.411 0.229 0.173 RMSE (CNN-Topo) 0.9870.793 0.865 0.968

Table 2: MAPE of ΔU^+ prediction, SSIM, and RMSE averaged over samples of each surface type.

the CNN feature maps, similar to those in the DNS drag maps. The pattern is also similar to the area distribution of roughness elements facing the flow in the corresponding topographical map, particularly visible in figure 8(b). This provides significant evidence of the ability of the CNN to predict drag, considering that the mechanism of drag induction on rough surfaces and the effective slope in the x-direction predominantly influence the pressure drag. Additionally, it demonstrates that the CNN model learned to determine the flow direction without being provided with any flow-related information.

To analyze these patterns further, we visualized the DNS drag maps and CNN feature maps in three dimensions (see figure 9). The DNS drag maps in figure 9 reveal a distinct concentration of \tilde{f}_x on positive slopes when viewed in the direction of the flow. This is particularly evident for roughness elements with positive slopes and heights exceeding the mean surface level, where the pressure drag is more pronounced than the viscous drag (Napoli & Armenio 2008). Conversely, the drag distribution observed in the opposite direction shows lower concentrations, attributable to the reduced presence of \tilde{f}_x . Similarly, the CNN feature maps in figure 9 effectively reflect this distribution, focusing on the wall-normal structures similar to the DNS drag maps. The model highlights the force disparity between the flow and counterflow directions. This alignment underscores the capability of our model to capture the topographical features critical to predicting ΔU^+ , demonstrating its ability to recognize spatial patterns in surface structures that predominantly induce pressure drag, even without information about the drag distribution or turbulent flow.

However, there are notable discrepancies in the drag force distributions on the planes of the CNN feature maps compared with those of the DNS drag maps. Generally, the plane areas of the CNN feature maps of figure 9 display lower values compared with those of the DNS drag maps. These divergences highlight the limitations of the CNN model in accurately predicting drag distributions for components beyond pressure drag. Additionally, the CNN model struggles to capture areas that are sheltered behind other roughness peaks and experience negligible local drag force, referred to as shadowed areas (Yang *et al.* 2022). Figure 10 shows the line graphs of the DNS drag map, CNN feature map, and topographical map at $z^+ = 23.5$, where the highest peak in the topographical map for $S_{pos,2}$ is located. Boxes (a), (b), and (c) in the figure illustrate a reduction in local drag in the shadowed areas in the DNS drag map, whereas this reduction is either absent or less pronounced in the CNN feature map. This suggests that the model has not completely accounted for the physics associated with the shadowed areas.

In addition, we analyzed the three maps (topographical, CNN feature, and DNS drag maps) of each surface sample in the wavenumber domain. This analysis aims to compare the scale of the dominant spatial patterns in each map. First, we calculated the spanwise-

H. Shin, S.M. Khorasani, Z. Shi, J. Yang, S. Lee, and S. Bagheri



Figure 9: Visualization of the DNS drag map and CNN feature map in 3D, with panels (a) to (d) corresponding to surfaces $S_{Gauss,1}$, $S_{pos,1}$, $S_{ES_x,1}$, $S_{ES_z,1}$, respectively.



Figure 10: DNS drag map and topographical map (upper row) and CNN feature map and topographical map (lower row) at $z^+ = 23.5$ for $S_{pos,2}$. Boxes (a), (b), and (c) highlight the zones where neighboring peak structures in the front create prominent shadowed areas behind them.

$$\begin{array}{cccc} S_{Gauss} & S_{pos} & S_{ESx} & S_{ESz} \\ \text{CNN-DNS} & 6.518 & 7.303 & 7.798 & 7.112 \\ \text{CNN-Topo} & 13.184 & 10.137 & 11.980 & 10.219 \end{array}$$

Table 3: Average ED of $k_x^+ \Phi$ between the DNS drag maps and the CNN feature maps (top) and the topographical maps and the CNN feature maps (bottom) of three samples.

averaged premultiplied power spectral density (PSD), denoted by $k_x^+ \Phi$. We assessed the similarity of $k_x^+ \Phi$ between the topographical, CNN feature, and DNS drag maps. The similarity between two different $k_x^+ \Phi$ (i.e. $k_x^+ \Phi_1$ and $k_x^+ \Phi_2$) is quantified using the Euclidean distance (ED), calculated as follows:

$$ED = \sqrt{\sum_{i=0}^{N_x} \left[k_x^+ \Phi_{1,i} - k_x^+ \Phi_{2,i} \right]^2}.$$
(4.15)

Figure 11 shows the $k_x^+ \Phi$ lines of the topographical maps, DNS drag maps, and CNN feature maps, and table 3 presents the calculated ED between the CNN feature map and both the DNS drag map and the topographical map for all the sampled surfaces. For the CNN feature map, $k_x^+ \Phi$ closely resembles that of the DNS drag map, indicating that the CNN feature map has similar dominant spatial patterns. Furthermore, we analyzed the similarities in the peaks of $k_x^+ \Phi$. For example, in $S_{Gauss,1}$, the wavenumbers of the three primary peaks of $k_x^+ \Phi$, identified by their highest values, are as follows: 0.084, 0.157, and 0.099 for the DNS drag map; 0.147, 0.199, and 0.094 for the CNN feature map; and 0.052, 0.037, and 0.079 for the topographical map. Subsequently, the λ_x^+ values are 75.0, 16



Figure 11: Streamwise-averaged $k_x^+ \Phi$ profiles for each surface type, depicted using a topographical map (-----), CNN feature map (-----), and DNS drag map (-----).

40.0, and 63.158 for the DNS drag map; 42.857, 31.579, and 66.667 for the CNN feature map; and 120, 171.429, and 80.0 for the topographical map. This analysis suggests a closer alignment in peak distribution between the DNS drag map and the CNN feature map compared with that between the CNN feature map and the topographical map. Thus, the critical patterns in both the CNN feature map and the DNS drag map exhibit similar scales. Figure 12 shows the five predominant λ_x^+ values in the $k_x^+ \Phi$ of the CNN feature map, which closely aligns with the scale of the drag force pattern identified in the DNS drag map. In the topographical map, these λ_x^+ values closely represent the distances between adjacent peaks and the size of streamwise peaks, both of which are crucial in influencing the pressure drag.

Additionally, we analyzed the two-dimensional premultiplied PSD $(k_x^+ k_z^+ \Phi)$, which are shown in figure 13. The similarities of the patterns in the samples $k_x^+ k_z^+ \Phi$ were evaluated using the SSIM and RMSE, as presented in table 4. This table indicates that, for all the



Figure 12: Top five $k_x^+ \Phi$ peak points $\lambda_x^+ (\lambda_{x,1}^+ \sim \lambda_{x,5}^+)$ identified in the CNN feature map compared across the (a) CNN feature map, (b) DNS drag map, and (c) topographical map for $S_{Gauss,1}$. The specific values for each λ_x^+ are as follows: $\lambda_{x,1}^+=42.857$, $\lambda_{x,2}^+=31.579$, $\lambda_{x,3}^+=66.667$, $\lambda_{x,4}^+=50.0$, and $\lambda_{x,5}^+=35.294$.

	S_{Gauss}	S_{pos}	S_{ES_x}	S_{ES_z}
CNN - DNS	0.424	0.345	0.784	0.753
CNN - Topo	0.350	0.322	0.644	0.584
CNN - DNS	0.070	0.082	0.046	0.051
${\rm CNN}$ - ${\rm Topo}$	0.080	0.078	0.052	0.058

Table 4: Comparison of $k_x^+ k_z^+ \Phi$ using the average SSIM (top) and RMSE (bottom) of three samples.

samples, the SSIM between the $k_x^+ k_z^+ \Phi$ of the DNS drag map and that of the CNN feature map is higher than that between the $k_x^+ k_z^+ \Phi$ of the CNN feature map and that of the topographical map, except for $S_{pos,3}$. In terms of the RMSE, the values are generally lower between the CNN feature maps and the DNS drag maps, except for $S_{pos,1}$, $S_{pos,2}$, and $S_{ES_x,2}$. Both the RMSE and SSIM metrics corroborate the findings from the $k_x^+ \Phi$ analysis, demonstrating a resemblance between the CNN feature maps and the DNS drag maps. Figure 13 not only confirms the congruence of the CNN feature maps with the DNS drag maps in terms of a high-intensity distribution but also highlights significant similarities in this distribution with the topographical maps. For instance, the marked boxes in $S_{ES_x,1}$ of figure 13 show common distribution patterns between the DNS drag and the CNN feature maps, and between the topographical and the CNN feature maps, also capturing distributions common to all the maps. This underscores the capability of the CNN model to extract dominant spatial features in surface topography and identify



H. Shin, S.M. Khorasani, Z. Shi, J. Yang, S. Lee, and S. Bagheri Topographical map CNN feature map DNS drag map

Figure 13: $k_x^+ k_z^+ \Phi$ of the topographical-, CNN feature-, and DNS drag maps, regarding $S_{Gauss,1}$, $S_{pos,1}$, $S_{ES_x,1}$, and $S_{ES_z,1}$. The marked box areas denote regions of similar high-intensity distributions between the topographical maps and the CNN feature maps (yellow boxes), between the DNS drag maps and the CNN feature maps (green boxes), and across all three types of maps (red boxes).

the essential scales of spatial patterns for predicting ΔU^+ over rough surfaces. Therefore, we will extract the parts that affect drag from the topographical map to determine which elements of the topographical map our CNN focuses on intensively to predict drag.

4.3. Topographical-characteristics-based analysis

We conducted an analysis using topographical characteristics maps, distinct from CNN feature maps, to identify specific topographical characteristics captured by the CNN model for predicting ΔU^+ . These maps, comprising a range of topographical elements,

18

were combined with distinct weights and subsequently visualized. This combination aimed to create a "composite map" resembling the CNN feature map, thereby elucidating the topographical characteristics essential to the predictive accuracy of the model.

The foundation of this analysis lies in the topography-derived maps, which encompass both the roughness height and the surface gradient map. The composite map comprises six base maps: T^t , T^b , T^m , G^t_x , G^m_x , and G^b_x . Here, T denotes the topographical map, and G_x , representing the gradient of T, is calculated as follows:

$$G_x = \frac{\partial T}{\partial x} \approx \frac{T_{\rm fw} - T_{\rm bk}}{2\Delta x},\tag{4.16}$$

where T_{fw} and T_{bk} denote the forward and backward positions by one grid point on the input map, respectively. The superscripts (t, b, and m) for T and G_x differentiate the maps based on specific thresholds. For example, T^t represents the values in the top 25% of all T values, T^b identifies those in the bottom 25%, and T^m includes the values between the bottom 25% and the top 25%.

We combined these base maps to create a composite map. This process involved merging two base maps, resulting in nine additional combination maps: $T^t G_x^t$, $T^t G_x^b$, $T^t G_x^m$, $T^m G_x^t$, $T^m G_x^b$, $T^m G_x^m$, $T^b G_x^t$, $T^b G_x^b$, and $T^b G_x^m$. For instance, $T^t G_x^t$ represents the integration of the top 25% of T values with the top 25% of gradient values from G_x . These maps were standardized using equation 4.1. Subsequently, we determined the optimal weights, w_i (where i = 1, 2, ..., 15), to determine the most effective combination ratio that reflects the CNN feature map. This was achieved using the following equation:

$$\mathbf{m}_{c} = w_{1}\tilde{T^{t}} + w_{2}\tilde{T^{m}} + w_{3}\tilde{T^{b}} + \dots + w_{15}T^{b}\tilde{G}_{x}^{b}, \tag{4.17}$$

where m_c represents the composite map created using the topographical characteristics maps to resemble the CNN feature map. We used stochastic gradient descent for the optimization of the weights (w_1 to w_{15}). This method iteratively refines the weights using the least squares method, which measures the difference between \mathbf{m}_c and the CNN feature maps. During each iteration, a subset of data is used to calculate the gradient of the loss function with respect to \mathbf{w} , guiding the adjustments required to better align with the CNN feature map. The weight update follows the equation:

$$\mathbf{w}_{\text{new}} = \mathbf{w}_{\text{old}} - \eta \cdot \nabla_w L(\mathbf{w}_{\text{old}}), \tag{4.18}$$

where \mathbf{w}_{new} and \mathbf{w}_{old} are the updated and previous weight vectors, respectively, η is the learning rate, and $\nabla_{\mathbf{w}} L(\mathbf{w}_{\text{old}})$ is the gradient of the loss function L with respect to \mathbf{w} at the previous iteration.

Figure 14 shows the optimized weights for each topographical characteristics map. According to this figure, the two most prominent surface features across various surface types are T^t and $T^t G_x^t$. Given that high roughness elements and positive gradients in the streamwise direction significantly influence pressure drag, this analysis suggests that the CNN model predominantly focuses on the topographical elements of rough surfaces that induce pressure drag to predict ΔU^+ . This is consistent with the analysis in the previous sections, where high values were distributed in the counterflow areas of roughness elements.

Accordingly, the results discussed in this section corroborate the analyses presented in the preceding section 4.1, demonstrating that our model primarily focuses on the peaks of rough surfaces and the positive gradients of these peaks in the direction of fluid flow. Therefore, given the close correlation between pressure drag for roughness heights larger than the viscous sublayer and the frontal area of rough surfaces, our model focuses on the pressure drag on rough surfaces. This analysis aligns with the findings of previous



Figure 14: Optimized $|\mathbf{w}|$ values of the composite map for each surface sample: (a) $S_{Gauss,1}$, (b) $S_{pos,1}$, (c) $S_{ES_x,1}$, and (d) $S_{ES_z,1}$.

studies (Jouybari *et al.* 2022; Chung *et al.* 2021; Orlandi & Leonardi 2006), which have shown that pressure drag significantly contributes to the total drag in a fully rough regime. Additionally, the less precise distribution of CNN feature maps in planar areas of rough surfaces or regions below the mean height indicates the limitations of the model in addressing forces other than the pressure drag. Moreover, our model does not accurately represent the force weakening in the shadowed areas of rough surfaces. In the following section, we will explore drag prediction on surfaces with negative skewness, where the pressure drag is not the predominant factor, unlike on other surfaces analyzed in previous sections, to clarify the limitations of our model further.

4.4. Limitations in predicting negative-skw surfaces

Although our CNN model has proven effective in predicting ΔU^+ based on the mechanism of the drag inducement for S_{Gauss} , S_{pos} , S_{ES_x} , and S_{ES_z} , it encounters challenges in accurately predicting S_{neg} when compared with these surface types. As indicated in table 1, the MAPE for S_{neg} is almost twice as high as that for the other surfaces. More importantly, the similarity between the DNS drag maps and CNN feature maps for S_{neg} is significantly lower than that for the other surface types (see figure 15).



Figure 15: Visualization of the topographical, DNS drag, and CNN feature maps for $S_{neg,1}.$



Figure 16: Visualization of the DNS drag and CNN feature maps on a topographical map in 3D for $S_{neg,1}$.

Consequently, this section discusses these limitations and investigates the reasons behind the reduced prediction accuracy and limited physics learnability for S_{neg} .

In the DNS drag maps of figure 15 and figure 16, the pits in the DNS map exhibit lower values than the planes, whereas in the CNN feature map, the pits show higher values than the planes. This occurs because the model fails to capture accurately the dominant



Figure 17: $k_x^+ \Phi$ profiles for S_{neg} , depicted using the topographical map (-----), CNN feature map (-----), and DNS drag map (-----).



Figure 18: $k_x^+ k_z^+ \Phi$ of the topographical maps, CNN feature maps, and DNS drag maps, regarding $S_{neg,1}$. The marked box areas denote regions of similar high-intensity distributions between the topographical maps and the CNN feature maps (yellow boxes), between the DNS drag maps and the CNN feature maps (green boxes), and across all three types of maps (red boxes).

physics of turbulent drag on S_{neg} surfaces, primarily focusing on regions with positive slopes and peaks while neglecting the plane and pit regions, similar to its performance in predicting the drag on $S_{Gauss}, S_{pos}, S_{ES_x}, S_{ES_z}$. Specifically, for S_{neg} , the average of the absolute SSIM between the sampled topographical maps and the CNN feature maps is 0.039, and that between the sampled DNS drag maps and the CNN feature maps is 0.058. These values are lower than the SSIM values between the CNN feature maps and the DNS drag maps compared with other surface types, as shown in table 2, where the average absolute SSIM for all types is 0.492.

According to the wavenumber domain analysis, S_{neg} shows a closer alignment of the CNN feature map with the topographical map than with the DNS drag map unlike other surface types (see figure 17). Specifically, the average ED between the sampled topographical map and the CNN feature map was 3.920, which is smaller than the ED between the sampled DNS drag map and the CNN feature map, which was 10.231. In other words, the scale of spatial patterns in the CNN feature map of S_{neg} more closely resembles that in the topographical map, diverging from the distributions observed in the DNS drag map. This congruence is also evident in the $k_x^+ k_z^+ \Phi$ (see figure 18). These results suggest that the CNN model did not accurately capture the spatial patterns for S_{neg} , unlike other previously analyzed surface types.

From an examination of previous studies, the inaccurate prediction of S_{neq} can be

attributed to several factors. According to Busse (2023), the ratio of the pressure drag force (F_p) to the total drag force (F_{tot}) , which includes both viscous and pressure drag forces, is higher for surfaces with positive or zero-skw values than for those with negativeskw values. Specifically, on surfaces with negative-skw values, characterized by planar and pit features similar to our S_{neg} , the F_p/F_{tot} ratio is reported to be smaller than 0.3. This suggests a relatively minor role of F_p in F_{tot} for S_{neq} compared with the surfaces with zero or positive-skw values. The study by Flack & Schultz (2020b) explored the influence of skewness on the drag of rough surfaces. The authors discovered that peak-dominant surfaces, or rough surfaces with skw values ranging from zero to positive, induce a higher drag compared with surfaces with negative-skw values. They proposed that the lower drag induction on negative-skw surfaces is due to flow skimming over surface depressions. Thus, the limited accuracy of the CNN model in predicting S_{neg} surfaces, coupled with its diminished ability to capture physics beyond the pressure drag distribution, highlights its limited focus on learning the pressure drag when predicting ΔU^+ and its reduced understanding of other factors influencing the total drag. Furthermore, the complex flow phenomena inherent to S_{neq} , as described by Jiménez (2004), contribute to the challenges of predicting and understanding the physics of S_{neq} . Surfaces with negative-skw values, featuring grooves and classified as either k-type or d-type based on their groove aspect ratio, exhibit complexities owing to recirculation vortices affecting the logarithmic layer offset. These complexities highlight the limitations of both the CNN model and the dataset in comprehensively understanding and learning the intricate flow dynamics of S_{neg} .

5. Conclusion

This study demonstrates the effectiveness of CNNs in predicting ΔU^+ , a critical parameter for evaluating turbulent drag on rough surfaces induced by fluid flow. The key findings of this study include the following:

(i) Our developed CNN model predicts ΔU^+ using only the rough surface topography as input, eliminating the need for extracting surface parameters and manually selecting them.

(ii) The feature map generated by our CNN model closely resembles the DNS drag maps, which indicate the distribution of drag generated by a flow over a rough surface. The model primarily identifies regions with high roughness elements. Additionally, it focuses on positive slopes in the wall-normal direction of roughness elements, which are linked with the frontal area of the rough surfaces and are strongly correlated with the pressure drag. Consequently, the CNN feature map exhibits elongated patterns in the spanwise direction, which are also observed in the DNS drag maps. Therefore, our model predicts drag based on the main mechanism of the drag induced on rough surfaces, which has positive or zero skewness.

(iii) Although our CNN model effectively predicts ΔU^+ for surfaces where the pressure drag is dominant, it exhibits diminished predictive accuracy for surfaces with negative skewness, where the pressure drag is not the primary source of drag. Additionally, the CNN feature map shows reduced similarity to the DNS drag maps for surfaces with negative skewness. This underscores the limitations of the CNN model in capturing the drag mechanisms of surfaces where pressure drag is not the predominant factor. Additionally, flow phenomena other than pressure drag, such as the effects of shadowed areas or recirculation vortices in negatively skewed surface pits, are not well captured.

Future studies should aim to improve the learnability of ANNs for complex physics of drag on rough surfaces to enable more robust and accurate drag predictions across differ-

	GCS_{base}	GCS_{coarse}	GCS_{fine}
N_y	312	156	770
$\Delta y_{\min}^+; \Delta y_{\max}^+$	1.051; 8.283	1.051; 16.563	0.422; 3.375

Table 5: *y*-directional grid resolutions utilized in the grid convergence study. GCS_{base} represents the grid resolution employed in this study, GCS_{coarse} is a grid resolution half that of GCS_{base} , and GCS_{fine} is a grid resolution twice that of GCS_{base} .

ent surface types. This objective requires expanding the training dataset to encompass a wider variety of rough surface patterns, such as k- and d-type negative skewness surfaces and nonhomogeneous rough surfaces such as those introduced by Medjnoun & Vanderwel (2018). Furthermore, considering that the rough surfaces in this study are comprised solely of randomly arranged roughness elements, integrating data on surfaces with regular arrangements into the dataset, as suggested by the study of Womack et al. (2022), could enhance the diversity of the dataset. Additionally, developing a larger training dataset is essential for utilizing feature extraction through the "vision transformer," which has recently demonstrated significant capabilities in computer vision. Moreover, although this study primarily investigated surfaces increasing drag ($\Delta U^+ > 0$), the inclusion of surfaces that decrease drag ($\Delta U^+ < 0$) under certain conditions, such as riblets (Bechert et al. 1997; García-Mayoral 2011), could offer valuable insights into the dynamics of rough surfaces. This strategy could assist in designing surfaces to minimize drag, by employing machine-learning methods. Furthermore, based on this study, we aim to develop a prediction model capable of visualizing drag distribution and instantly predicting the flow drag generated on the surface by processing diverse images of rough surfaces.

Acknowledgements

This work was supported by Korea Institute of Energy Technology Evaluation and Planning(KETEP) grant funded by the Korea Government(MOTIE) (RS-2023-00243974, Graduate School of Digital-based Sustainable Energy Process Innovation Convergence), the National Research Foundation of Korea Grant funded by the Korean Government(NRF-2022R1F1A1066547), and the Inha University Research Grant. SMHK, ZS and SB acknowledge the National Academic Infrastructure for Supercomputing in Sweden (NAISS) and the Swedish Energy Agency for funding the research.

Declaration of interests

The authors report no conflict of interest.

Appendix A. Validation of the DNS solver

We employed the same resolution criteria as those reported in Jouybari *et al.* (2021) and Yuan (2014). We validated the grid convergence of the DNS solver by halving and doubling the y grid numbers used in this study. The grid numbers and resolutions utilized in this grid convergence test are summarized in table 5. Figure 19 illustrates the mean velocity profile in the x-direction for each grid resolution. When GCS *fine* is



Figure 19: Mean streamwise velocity profile of each different grid resolution: ———, GCS_{base}; ———, GCS_{coarse}; ———, GCS_{fine}.

considered as the ground truth, the absolute percentage errors at y_{ref} are 0.969% for GCS_{base} and 0.808% for GCS_{coarse} .

Appendix B. Architectural features of the CNN model

The architecture of our model was designed to include several important features. First, it utilizes a residual network (ResNet) framework, as proposed by He *et al.* (2016), which is extensively employed to address the vanishing gradient problem. Second, it adopts periodic boundary padding to reflect the periodic boundary condition used in DNS, ensuring consistency between the simulation and the model input. Third, the architecture uses GAP to create a feature map that effectively emphasizes critical areas on the rough surface that are important for predicting ΔU^+ . Finally, it features a parallel structure with various kernel sizes to improve the ability of the model to detect features of rough surfaces at different scales.

The ResNet architecture incorporates skip connections, which create direct pathways to previous layers, effectively addressing the vanishing gradient problem. This problem involves the diminishing gradients of the loss function during the training of deep neural networks, leading to minimal parameter updates. The skip connections mitigate this issue by ensuring a consistent and effective flow of gradients throughout the network.

GAP, as outlined by Zhou *et al.* (2016), is crucial for generating a two-dimensional feature map that highlights significant regions in the data, thereby aiding the decisionmaking processes of the CNN. By employing this pooling method, our CNN constructs a feature map that significantly contributes to the prediction of ΔU^+ from the input rough surface. This representation, termed a "CNN feature map" in this study, indicates significant areas on rough surfaces utilized by our CNN model for drag prediction.



Figure 20: Illustration of augmentation via mirroring. (a) Original surface and (b) mirrored counterpart along the streamwise axis.



Figure 21: Partitioning of dataset into training, validation, and test subsets.

Appendix C. Data preprocessing

C.1. Data augmentation

Hydrodynamically smooth surfaces, denoted as S_{smooth} , were included to enhance the diversity of the dataset. As U_R^+ in equation 2.6 equals U_S^+ for these surfaces, the resulting ΔU^+ is consistently zero. This allowed us to create a smooth surface dataset without using additional DNS.

Furthermore, the dataset was expanded by reflecting surfaces along the x-axis. This mirrored surface retains its original ΔU^+ value, making it suitable for augmentation. This strategy effectively doubles the dataset size without requiring additional computations. Figure 20 illustrates the original and mirrored surfaces.

C.2. Data partitioning

The expanded dataset of topographical maps was divided into training, validation, and test sets in the proportions of 60%, 20%, and 20%, respectively, as illustrated in figure 21. To optimize model training and minimize biases, the rough surfaces and their corresponding ΔU^+ values were randomly shuffled. This procedure ensured an even distribution of data throughout the CNN training phase. All the data were then standardized using equation 4.1, based on the mean and variance of the training dataset.

Appendix D. Optimization of hyperparameters

The optimization of hyperparameters is essential for improving the performance of ANNs. A thorough analysis of these parameters was performed to refine the CNN model. Bayesian optimization (BO) was employed for this purpose. BO uses a probabilistic model to predict the performance of the objective function, enabling an efficient exploration of the hyperparameter space. This method is particularly beneficial in scenarios involving high-dimensional optimization, where exhaustive searches are computationally infeasible. In this study, the hyperparameters optimized for the CNN model through BO include $N_b = 3$ and $N_f = 48$, where N_f represents the number of filters, and N_b denotes the number of ResNet blocks.

REFERENCES

- BECHERT, D. W., BRUSE, M., HAGE, W. V. & VAN DER HOEVEN, J. T. & HOPPE, G. 1997 Experiments on drag-reducing surfaces and their optimization with an adjustable geometry. *Journal of fluid mechanics* 338, 59–87.
- BUSSE, A. & JELLY, T. O. 2023 Effect of high skewness and kurtosis on turbulent channel flow over irregular rough walls. *Journal of Turbulence* **24** (1-2), 57–81.
- CHAN, L., MACDONALD, M., CHUNG, D., HUTCHINS, N. & & OOI, A. 2015 A systematic investigation of roughness height and wavelength in turbulent pipe flow in the transitionally rough regime. *Journal of Fluid Mechanics* **771**, 743–777.
- CHUNG, D., CHAN, L., MACDONALD, M. & HUTCHINS, N. & OOI, A. 2015 A fast direct numerical simulation method for characterising hydraulic roughness. *Journal of Fluid Mechanics* 773, 418–431.
- CHUNG, D., HUTCHINS, N. & SCHULTZ, M. P. & FLACK, K. A. 2021 Predicting the drag of rough surfaces. Annual Review of Fluid Mechanics 53, 439–471.
- CLAUSER, F. H. 1954 Turbulent boundary layers in adverse pressure gradients. Journal of the Aeronautical Sciences 21 (2), 91–108.
- COSTA, P., PHILLIPS, E. & BRANDT, L. & FATICA, M. 2021 Gpu acceleration of cans for massively-parallel direct numerical simulations of canonical fluid flows. *Computers & Mathematics with Applications* 81, 502–511.
- DEO, I. K. & JAIMAN, R. 2022 Predicting waves in fluids with deep neural network. *Physics of Fluids* **34** (6).
- FLACK, K. A. & SCHULTZ, M. P. & BARROS, J. M. 2020a Skin friction measurements of systematically-varied roughness: probing the role of roughness amplitude and skewness. *Flow, Turbulence and Combustion* 104, 317–329.
- FLACK, K. A. & SCHULTZ, M. P. & VOLINO, R. J. 2020b The effect of a systematic change in surface roughness skewness on turbulence and drag. *International Journal of Heat and Fluid Flow* **85**, 108669.
- FOROOGHI, P., STROH, A., MAGAGNATO, F. & JAKIRLIĆ, S. & FROHNAPFEL, B. 2017 Toward a universal roughness correlation. *Journal of Fluids Engineering* **139** (12), 121201.
- GARCÍA-MAYORAL, R. & JIMÉNEZ, J. 2011 Drag reduction by riblets. Philosophical transactions of the Royal society A: Mathematical, physical and engineering Sciences 369 (1940), 1412– 1427.
- HAMA, F. R. 1954 Boundary layer characteristics for smooth and rough surfaces. Trans. Soc. Nav. Arch. Marine Engrs. 62, 333–358.
- HE, K., ZHANG, X. & REN, S. & SUN, J. 2016 Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 770–778.
- JACOBS, T. D. & JUNGE, T. & PASTEWKA, L. 2017 Quantitative characterization of surface

topography using spectral analysis. Surface Topography: Metrology and Properties 5 (1), 013001.

- JELLY, T. O. & BUSSE, A. 2019 Multi-scale anisotropic rough surface algorithm: technical documentation and user guide. University of Glasgow.
- JIMÉNEZ, J. 2004 Turbulent flows over rough walls. Annu. Rev. Fluid Mech. 36, 173–196.
- JOUYBARI, M. A., SEO, J. H., YUAN, J. & MITTAL, R. & MENEVEAU, C. 2022 Contributions to pressure drag in rough-wall turbulent flows: Insights from force partitioning. *Physical Review Fluids* 7 (8), 084602.
- JOUYBARI, M. A., YUAN, J. & BRERETON, G. J. & MURILLO, M. S. 2021 Data-driven prediction of the equivalent sand-grain height in rough-wall turbulent flows. *Journal of Fluid Mechanics* 912, A8.
- KAJISHIMA, T., TAKIGUCHI, S. & HAMASAKI, H. & MIYAKE, Y. 2001 Turbulence structure of particle-laden flow in a vertical plane channel due to vortex shedding. JSME International Journal Series B Fluids and Thermal Engineering 44 (4), 526–535.
- KIM, J. & MOIN, P. 1985 Application of a fractional-step method to incompressible navierstokes equations. *Journal of computational physics* 59 (2), 308–323.
- LEE, S. & YOU, D. 2019 Data-driven prediction of unsteady flow over a circular cylinder using deep learning. Journal of Fluid Mechanics 879, 217–254.
- LEE, S., YANG, J., FOROOGHI, P. & STROH, A. & BAGHERI, S. 2022 Predicting drag on rough surfaces by transfer learning of empirical correlations. *Journal of Fluid Mechanics* 933, A18.
- MEDJNOUN, T. & VANDERWEL, C. & GANAPATHISUBRAMANI, B. 2018 Characteristics of turbulent boundary layers over smooth surfaces with spanwise heterogeneities. *Journal* of Fluid Mechanics 838, 516–543.
- MORIMOTO, M., FUKAMI, K., ZHANG, K. & NAIR, A. G. & FUKAGATA, K. 2021 Convolutional neural networks for fluid flow analysis: toward effective metamodeling and low dimensionalization. *Theoretical and Computational Fluid Dynamics* 35 (5), 633–658.
- MURATA, T. & FUKAMI, K. & FUKAGATA, K. 2020 Nonlinear mode decomposition with convolutional neural networks for fluid dynamics. *Journal of Fluid Mechanics* 882, A13.
- NAPOLI, E. & ARMENIO, V. & DE MARCHIS, M. 2008 The effect of the slope of irregularly distributed roughness elements on turbulent wall-bounded flows. *Journal of Fluid Mechanics* 613, 385–394.
- ORLANDI, P. & LEONARDI, S. & ANTONIA, R. A. 2006 Turbulent channel flow with either transverse or longitudinal roughness elements on one wall. *Journal of Fluid Mechanics* 561, 279–305.
- SANTOS, J. E., XU, D., JO, H., LANDRY, C. J. & PRODANOVIĆ, M. & PYRCZ, M. J. 2020 Poreflow-net: A 3d convolutional neural network to predict fluid flow through porous media. Advances in Water Resources 138, 103539.
- SZEGEDY, C., LIU, W., JIA, Y., SERMANET, P., REED, S., ANGUELOV, D., ERHAN, D. & VANHOUCKE, V. & RABINOVICH, A. 2015 Going deeper with convolutions. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 1–9.
- THAKKAR, M. & BUSSE, A. & SANDHAM, N. 2017 Surface correlations of hydrodynamic drag for transitionally rough engineering surfaces. *Journal of turbulence* **18** (2), 138–169.
- WANG, Z., BOVIK, A. C. & SHEIKH, H. R. & SIMONCELLI, E. P. 2004 Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing* 13 (4), 600–612.
- WOMACK, K. M., VOLINO, R. J. & MENEVEAU, C. & SCHULTZ, M. P. 2022 Turbulent boundary layer flow over regularly and irregularly arranged truncated cone surfaces. *Journal of Fluid Mechanics* 933, A38.
- YANG, J., STROH, A. & CHUNG, D. & FOROOGHI, P. 2022 Direct numerical simulationbased characterization of pseudo-random roughness in minimal channels. *Journal of Fluid Mechanics* 941, A47.
- YUAN, J. & PIOMELLI, U. 2014 Estimation and prediction of the roughness function on realistic surfaces. Journal of Turbulence 15 (6), 350–365.
- ZHOU, B., KHOSLA, A., LAPEDRIZA, A. & OLIVA, A. & TORRALBA, A. 2016 Learning deep features for discriminative localization. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 2921–2929.